

Table 1: AppController Command Switches for Application

| Switch | Intended Recipient | Source | Platform (Windows or UNIX) |
|------------------------|---|--------------------------|----------------------------------|
| /f <filename> | open a file | Cmnd-Line & Mail Slot | Both |
| /fr <filename> | open a file read-only | Cmnd-Line & Mail Slot | Windows |
| /ft <filename> | open a file and track changes visibly | Cmnd-Line & Mail Slot | Both |
| /fi <filename> | open a file and track changes invisibly | Cmnd-Line & Mail Slot | Both |
| /c | close all files, save them | Mail Slot | Both |
| /c <filename> | close filename, save it | Mail Slot | Both |
| /cnosave | close all files, do not save | Mail Slot | Both |
| /cnosave <filename> | close filename, do not save | Mail Slot | Both |
| /p <filename> | print a file | Cmnd-Line & Mail Slot | Both |
| /d "info" | Retrieves application information (MS Office Apps only) | Mail Slot | Windows |
| /i | Make application invisible | Mail Slot | Windows |
| /v | Make application visible | Mail Slot | Windows |

Table 2: Command Switches for AppController

| Switch | Intended Recipient | Source | Platform (Windows or UNIX) |
|---------------------|--|-----------------------|-------------------------------|
| /a < app code> | start an application | Cmnd-Line | Both |
| /m <mail-slot name> | partial mail-slot name, AppController will append the Terminal Server session user-id to this string to guarantee uniqueness | Cmnd-Line | Windows |
| /l 1,2, or 3 | logging level. Determines which errors get written to system Event Log. 0 = None 1 = Low, Errors only 2 = Medium, Errors and Warnings 3 = High, Errors, Warnings, and Informational | Cmnd-Line & Mail Slot | Windows |
| /x <.exe or .bat> | Run this program when AppController exits | Cmnd-Line | Both |
| /np | AppController will show a "Always On Top" popup window that shows a progress bar. The code behind this window searches for the Default Printer that Tarantella has assigned to this session. This switch prevents AppController from showing this window | Cmnd-Line | Windows |
| /dn <user-name> | Changes the displayed username key for this execution of AppController. Restores the username when this execution ends (MS Office Apps only) | Cmnd-Line & Mail Slot | Both |
| /visible | make program form visible | Mail Slot | Both |
| /invisible | make program form | Mail Slot | Both |

| | | | |
|-----------|---|-----------|---------|
| | invisible | | |
| /minimize | minimize program form | Mail Slot | Both |
| /maximize | maximize program form | Mail Slot | Both |
| /restore | restore program form | Mail Slot | Both |
| /unload | close all file (with save), stop listening to mail-slot, unload terminal server session | Mail Slot | Both |
| /quit | make listener stop listening to mail-slot | Mail Slot | Windows |